


PV884, PV885, PV888, PV889

ULTRA Broadband Video Baluns



Features/Advantages	Description	Applications
<ul style="list-style-type: none"> Transport ALL CATV spectrum video signals over UTP* Up to 120+ channels (850 MHz) in CATV spectrum Low-cost solution for moves, add-ons and changes by reducing cost of cable and associated labor Shielded metal enclosure Made in USA 100% tested 	<p>Expanding the applications opened by its Broadband Video Baluns, ETS introduces the PV884 and PV885 – ULTRA Broadband Video Baluns. Frequency range has been increased and EMI reduced, both due to enhanced filtering and an all-metal enclosure.</p> <p>FCC requirements preclude boosting signal levels to the values required to guarantee preset distances. Distance achievable is a function of signal level, balance and the degree to which the cable used unbalances the signal. Cat5e maintains signal balance at least 5 dB better than Cat5. Level 7 or equivalent cable is another 5 dB better, providing for a signal drive level of not more than 46 dBmV.</p> <p>The PV884 offers a BNC connector for use with professional grade equipment. “Prosumer” and consumer electronics that connect using ‘F’ connectors require the ETS PV885 or PV888 baluns.</p>	<ul style="list-style-type: none"> Cable TV Distribution Media Retrieval Systems Schools Churches Production Monitoring Security and Surveillance Displays “Smart” Houses Teleconferencing

***NOTE:** Category 5e or better cable recommended. Other wiring may result in non-compliance with FCC rules and regulations.

Specifications		Product Ordering Information					
Bandwidth	20 MHz to 850 MHz CATV to 120+, off air channels 2 to 75	PV884	Ultra Broadband, female BNC to RJ45 pins 4, 5				
Connectors	BNC or F connector to RJ45	PV885	Ultra Broadband, female ‘F’ to RJ45 pins 4, 5				
Impedance	75Ω unbalanced to 100Ω balanced	PV888	Ultra Broadband, male ‘F’ on 6” pigtail to RJ45: 4, 5				
Insertion Loss	3 dB up to 350 MHz; 5 dB up to 850 MHz	PV889	Ultra Broadband, male ‘F’ on 6” pigtail to RJ45: 1, 2				
Return Loss	16 dB	PFA	F connector gender adapter, male to male				
Distance	130 ft up to 120 channels	‘Rough’ Cable Type v. Channel = Distance Chart					
Common Mode Rejection	>40 dB	chan. →	2	26	77	120	Signal Max
Media	Category 5e or better UTP	CAT5	180m	85m	50m	40m	36dBmV
Dimensions	25mm x 25mm x 70mm	CAT5e	215m	100m	60m	50m	41dBmV
Net Weight	0.07 kg	Level 7	280m	120m	70m	55m	46dBmV
			(or equivalent)				

© Copyright 2004-2011 Energy Transformation Systems, Inc. FatCat5 System panels and information outlets protected under US Patent Number 6,123,577. FatCat5™, FatCat5 System™, Chameleon Color Coding System™, Balanced Star™, Balanced Line™, Monoline™ and Precision Wave™, InstaSnake™, CineSnake™ are trademarks of Energy Transformation Systems. All other brand or product names are or may be trademarks of, and are used to identify the products or services of their respective owners.

Revised 11/07/2011



Energy Transformation Systems, Inc.
 43353 B Osgood Road, Fremont, CA 94539
 www.etslan.com
 800-752-8208 510-656-2012 Fax 510-656-2026

