
## **PA700 Series**

## **Analog Audio Distribution Hub**





| Features/Advantages   | Description  | Applications  |
|---|--|---|
| <ul> <li>Send stereo audio signals over Cat5 wiring</li> <li>Up to 512 outputs possible from a single source</li> <li>For efficiency, the system balances the input signal, distributes on UTP, and converts back at each receiver</li> <li>Complete system design flexibility, with components that can be several hundred feet apart</li> </ul> | The Cat5 Audio Broadcast System from ETS, the PA700 UTP Analog Audio Distribution Hub (pictured above) has two channels of line-level audio transmitted through the distribution amplifier, creating 8 output sets (stereo audio) from a single source.  The powered PA700 can be cascaded twice (three tiers), yielding a total distribution of 512 receivers from a single input source.  Audio signals are converted to and from UTP using the standard ETS PA807 Analog Audio Balun.  The PA700 System supports stereo audio over a total run length exceeding 100 meters (inclusive of all cable segments) on Category 5 or better cable. | <ul> <li>Home Theater Systems</li> <li>Meeting Halls</li> <li>Churches</li> <li>Schools</li> <li>Classrooms</li> <li>Auditoriums</li> <li>Healthcare Facilities</li> <li>Cruise Ships</li> <li>Factories</li> </ul> |
| Low power requirements for<br>the hubs: display baluns<br>need no external power  |  |   |
| Made in USA, 100% tested  |  |   |

| Specifications   |  | Product Ordering Information |  |
|--|--|------------------------------|--|
| Bandwidth  | 10Hz to 20kHz                                    | PA700                        | UTP Audio Stereo Distribution Hub, 8 Channel |
| Connectors   | (9) RJ45 jack s – (1) in (8) out                 |                              |  |
| Impedance  | 600:600  |                              |  |
| Isolation  | 500 V (per channel)                              |                              |  |
| Power In   | 9-12 VAC, 800mA min. with Power Adapter supplied |                              |  |
| Distance   | Up to 1000 ft.                                   |                              |  |
| Dimensions 260 mm x 165 mm x 32 mm (10.3 x 6.5 x 1.3 in) |  |                              |  |
| Net Weight   | 1.5 kg (3.40 Lbs)                                |                              |  |

© Copyright 1999-2011 Energy Transformation Systems. FatCat5 System panels and information outlets protected under US Patent Number 6,123,577. FatCat5<sup>TM</sup>, FatCat5 System<sup>TM</sup>, Chameleon Color Coding System<sup>TM</sup>, Balanced Star<sup>TM</sup>, Balanced Line<sup>TM</sup>, Monoline<sup>TM</sup> and Precision Wave<sup>TM</sup>, InstaSnake<sup>TM</sup>, CineSnake<sup>TM</sup> are trademarks of Energy Transformation Systems. All other brand or product names are or may be trademarks of, and are used to identify the products or services of their respective owners.

Revised 10/13/11



Energy Transformation Systems, Inc. 43353 B Osgood Road, Fremont, CA 94539 www.etslan.com 800-752-8208 510-656-2012 Fax 510-656-2026

