



Features/Advantages	Description	Applications
<ul style="list-style-type: none"> HDMI 1.3A, HDCP and RoHS compliant Extends up to 197 ft (60 m) at 1080i or 720p 60Hz Extends up to 131 ft (40 m) at 1080p 60Hz Passes inspection for in wall installations over 2 CAT5 or 6 cables Cable skew adjustable equalization with 8 levels Easy – Plug & Play Rugged metal cases One year warranty 	<p>The ETS HDMI CAT5/6 Extender (AV961G) gives excellent HD signal transmission with surround sound along with a high resolution picture. The ETS AV961G has signal transmission distances up to 197 ft (60m) for 1080i or 131ft (40 m) in 1080p HDMI format. Using two Cat5/6 cables, users can extend HDMI sources from sources compliant with TMDS connecting with distant display monitors including HDMI/DVI enabled TVs or LCD PC monitors.</p> <p>A permanent installation using Cat5 or 6 cables in the wall will pass building inspections. HDMI cables do not pass.</p> <p>To ensure the sharpest picture possible, the AV961G has a gain/equalization control switch to maximize the signal for the cable distance being used.</p> <p>The ETS HDMI CAT5/6 Extender includes (1) transmit, (1) receiver and 5V power supply. HDMI cables are sold separately. Available in 3 ft, 6 ft, 10 ft and 15 ft. Sold only in sets.</p>	<ul style="list-style-type: none"> Auditoriums Churches Classrooms Digital Signage Home Theaters Information Kiosks Conference Rooms Monitoring Stations Schools Trade Shows

Specifications		Product Ordering Information	
Video Bandwidth	2.25 Gbps (HDMI 1.3a)	AV961G	HDMI CAT5 Extender, (1) Transmit + (1) Receive and power supply (Only sold in sets.)
Connectors	HDMI female connector to (2) RJ45 jack with 2 indication LEDs	EC-HDMI-3	3.00 ft HDMI cable, male to male connector
Input TMDS signal	1.2 volts (peak to peak)	EC-HDMI-6	6.00 ft HDMI cable, male to male connector
Input DDC signal	5 volts (peak to peak)	EC-HDMI-10	10.00 ft HDMI cable, male to male connector
Equalizer selector	8 positions rotary dip switch (Receiver unit)	EC-HDMI-15	15.00 ft HDMI cable, male to male connector
Power Supply	5 volt 1A		
Media	Category 5 or better		
Distance	1080P – 165 ft; 1080i – 264 ft		
Dimensions (LWH)	70 x 66 x 25mm		
Net Weight	80g		

© Copyright 2008-2009 Energy Transformation Systems, Inc. FatCat5 System panels and information outlets protected under US Patent Number 6,123,577. FatCat5, FatCat5 System, Chameleon Color Coding System, Balanced Star, Balanced Line, Monoline and Precision Wave are trademarks of Energy Transformation Systems. All other brand or product names are or may be trademarks of, and are used to identify, products or services of their respective owners. Revised 07/-8/09



<http://www.etslan.com>

Energy Transformation Systems, Inc.
 43353 Osgood Rd. #B, Fremont, CA 94539
 800-752-8208 (US only) Fax 510-656-2026
 510-656-2012