


PV950

Isolated Video Balun



Features/Advantages	Description	Applications
<ul style="list-style-type: none"> Ideal for situations where differing ground potentials between send and receive units create ground loop conditions, degrading picture quality Use UTP for long distance signal transmission with superior performance and easy, low cost installation Distances <ul style="list-style-type: none"> Color > 330 meters B/W > 750 meters Greater stability with wider bandwidth (0 to 60 Mhz) Rugged plastic cases Made in USA 100% tested 	<p>The PV950 Isolated Video Balun from ETS is designed for baseband (CCTV), NTSC, PAL and SECAM signals. The PV950 blocks the effects of ground loops (the visual ripples and warps in the video image, often referred to as “hum bars”) when sending baseband video signals over Category 5 or better 100Ω twisted pair cabling (UTP or STP).</p> <p>The PV950 uses special circuitry (patent applied for) to block noise ingress at the point of entry to the Category 5 cabling, yielding a better transmission medium for baseband video, especially over the longer distances required by many current applications. The baluns, passive (no power required) devices, convert baseband signals from the 75Ω coax cabling of any source equipment. The PV950 creates a balanced signal and sends it over 100Ω UTP wiring, then converts back at the receiving end, yielding excellent picture quality.</p>	<ul style="list-style-type: none"> Many Baseband Video applications Security and Surveillance Video Terminals, Displays

Specifications	Product Ordering Information																						
<table> <tr><td>Bandwidth</td><td>6 Hz to 9.5 MHz</td></tr> <tr><td>Insertion Loss</td><td>1.3 dB</td></tr> <tr><td>Return Loss</td><td>19.4 dB</td></tr> <tr><td>Balance</td><td>40 dB</td></tr> <tr><td>Connectors</td><td>BNC (female or male) to RJ45 jack</td></tr> <tr><td>Media</td><td>Category 5 or better</td></tr> <tr><td>Distance</td><td>1200 ft – Color; 2500 ft – B/W</td></tr> <tr><td>Dimensions</td><td>66mm x 66mm x 28mm</td></tr> <tr><td>Net Weight</td><td>0.1 kg</td></tr> </table>	Bandwidth	6 Hz to 9.5 MHz	Insertion Loss	1.3 dB	Return Loss	19.4 dB	Balance	40 dB	Connectors	BNC (female or male) to RJ45 jack	Media	Category 5 or better	Distance	1200 ft – Color; 2500 ft – B/W	Dimensions	66mm x 66mm x 28mm	Net Weight	0.1 kg	<table> <tr> <td>PV950</td> <td>Isolated Baseband Video Balun, FBNC to RJ45, pins 5, 4</td> </tr> <tr> <td>PV951</td> <td>Isolated Baseband Video Balun, FBNC to screw terminal</td> </tr> </table>	PV950	Isolated Baseband Video Balun, FBNC to RJ45, pins 5, 4	PV951	Isolated Baseband Video Balun, FBNC to screw terminal
Bandwidth	6 Hz to 9.5 MHz																						
Insertion Loss	1.3 dB																						
Return Loss	19.4 dB																						
Balance	40 dB																						
Connectors	BNC (female or male) to RJ45 jack																						
Media	Category 5 or better																						
Distance	1200 ft – Color; 2500 ft – B/W																						
Dimensions	66mm x 66mm x 28mm																						
Net Weight	0.1 kg																						
PV950	Isolated Baseband Video Balun, FBNC to RJ45, pins 5, 4																						
PV951	Isolated Baseband Video Balun, FBNC to screw terminal																						

© Copyright 2001-2009 Energy Transformation Systems, Inc.
 FatCat5 System panels and information outlets protected under US Patent Number 6,123,577. FatCat5, FatCat5 System, Chameleon Color Coding System, Balanced Star, Balanced Line, Monoline and Precision Wave are trademarks of Energy Transformation Systems. All other brand or product names are or may be trademarks of, and are used to identify the products or services of their respective owners. Revised 07/07/2009



Energy Transformation Systems, Inc.
 43353B Osgood Road, Fremont, CA 94539
 www.etslan.com
 800-752-8208 510-656-2012 Fax 510-656-2026

